

Included in the package



--> Side Skirts (Pair)


--> Silicone

--> 8 X Screws



ABS



 We highly recommend having your products installed by a specialist.

## Installation

Resources  
needed!



Screwdriver - Masking Tape - Cloth - Pencil




At least two people




Around 40 min

Centering



Center the side skirt under the car's side to find the right place for the product to be installed. Use a pencil to draw an outline on the surface of the car around the product's edges. This will be used as an installation driver.

Cleaning




Clean the car's surface and the side skirt with cleaner. Let the surfaces dry.

Apply silicone



Apply silicone over the product's surface that attaches to the car. Then, re-center the side skirt following the drawn outline from the previous step.

 Excessive silicone could overflow and become visible once the side skirt is attached.

Attaching



Carefully place the side skirt on the car, following the marked outline, and attach the screws to their contact points. Screw the bolts while holding the side skirt to the right place.

Detailed attaching instructions

	<p><b>We recommend:</b></p> <p>--&gt; Adding silicone at maximum 5 cm from each edge of the side skirt.</p> <p>--&gt; Adding 6 to 8 spots of silicone, between the 2 mentioned above, at equal distance from each other.</p>
	<p>--&gt; Drilling at each side of the product, as shown in the picture.</p> <p>--&gt; Using 2 screws for each side of the product.</p>

**Securing**



Press and secure the side skirt with suitable strong adhesive tape.

**⚠ The adhesive tape should hold the product on the car tightly.**

**Repeat**

Repeat the steps for the other side skirt.

**Vehicle Use**

The vehicle is now ready to be used according to the instructions below.